

OAK STONE

(pictures for reference only, samples must be ordered separately)



WOOD SPECIES

Oak is a hard, strong and heavy, fairly straight-grained wood species. It is warm brown in colour, and its colour deepens over time. Given its weight, oak expands very little over time, making it a very popular interior design material.

Brinell hardness ~ 3.4-4.1 HB

PRODUCT

Oak Stone has a translucent grey hue. The strong grain and knot patterns give this product a rustic vintage look. The product is characterised by its strong variations in colour and grain structure, as well as the symmetric patterns typical for oak. An unlimited number of knots and cracks of unspecified sizes. Small depressions in dark filled knots and in cracks are also allowed.

DIMENSIONS (2.42 m² per package, 96.8 m² per pallet)

- Thickness: 14,5 mm
- Width: 185 mm
- Length: 2180 mm, supporting lengths of 1818 - 2080 mm also allowed (only one length per package)
- Top layer: 3,5 mm
- Weight: 9.6 kg/m²

STRUCTURE

- 1-strip wooden floor
- 0.7 mm micro bevels on the long sides,
- 0.5 mm micro bevels on the short sides
- Three-layer cross-glued structure:
- Top layer 3,5 mm
- Middle layer: plywood, 9 mm
- Bottom layer: Finnish spruce, 2 mm

3.5 mm
9.0 mm
2.0 mm



Standard products have a plywood structure

SURFACE TREATMENT OPTIONS

- UV-harneded wax oil
- brushed surface

INSTALLATION OPTIONS

- Floating installation (with underlay material) or glued down to subfloor (concrete or plywood)
- Locking system WiseLoc (must be glued in tongue and groove / Traditional Tongue and Groove)
- Suitable with underfloor heating

WiseLock 5G



QUALITY

- FINNISH quality – produced from start to finish in Finland, a Key Flag Symbol product
- PEFC – our timber comes from certified forests
- CE – our products fulfil the safety requirements of the applicable EU directives
- M1 – the best possible emission classification



