



LARCH

(pictures for reference only, samples must be ordered separately)

WOOD SPECIES

Larch is a valued softwood species. The colour of its heartwood is a reddish brown, while the sapwood is lighter in colour. Larch withstands wear better than pine. Larch is characterised by its significant colour variations and knottiness.

Brinell hardness ~ 1.9–2.5 HB

PRODUCT

In larch, the natural grain pattern and colour variation of the wood are clearly visible. In addition to natural knots, larch surfaces also feature oval knots, round knots and knots that have been treated with brown wood cement. The colour varies naturally from a light yellowish tone to a reddish colour. The rustic appearance of the wood evens out the variation.

DIMENSIONS (2.42 m² per package, 96.8 m² per pallet)

- Thickness: **14.5 mm**
- Width: **185 mm**
- Length: 2,180 mm, available length dimensions also include 2,080 mm, 2,000 mm and 1,818 mm (only one length per package)
- Surface layer: 3.5 mm
- Weight: 9.6 kg/m²

STRUCTURE

- Single-strip wooden floor
- 0.7 mm micro bevels on the long sides,
- 0.5 mm micro bevels on the short sides
- Three-layer cross-glued structure:
 - Surface layer 3.5 mm
 - Intermediate layer: domestic birch plywood, 9 mm
 - Base veneer: domestic spruce, 2 mm

3.5 mm
9.0 mm
2.0 mm



Standard products have a birch plywood structure

SURFACE TREATMENT OPTIONS

- UV-cured wax oil
- Nylon brushed surface

INSTALLATION OPTIONS

- Can be installed as either floating (underlay material required) or glued to the underlay (concrete or plywood).
- Locking tongue and groove WiseLock 5G
- The tongues and grooves are treated with a moisture-repellent wax to protect the seams.
- Suitable for installation on surfaces with underfloor heating.



QUALITY

- **FINNISH** quality – produced from start to finish in Finland, a Key Flag Symbol product
- Allergy Label – Timberwise products are the first and only products in their category to be awarded the Finnish Allergy, Skin and Asthma Federation's Allergy Label.
- PEFC – our timber comes from certified forests
- CE – our products fulfil the safety requirements of the applicable EU directives
- M1 – the best possible emission classification
- JAS2 – our adhesive joints meet the criteria for the most demanding industry standards
- JAS F**** – the highest and most stringent standard for formaldehyde emission testing, we use the formaldehyde-free EPI adhesive in our products



LARCH

