

erwise quality wooden floors from finland

Douglas Fir COTTON

brushed, hard wax oiled



WOOD SPECIE

Cotton Fir is a valued softwood species. The colour of its heartwood is reddish brown. The sapwood is light-coloured. The timber is characterised by the strongly developed heartwood and summerwood parts. One of the central characteristics of this wood species is its better wear resistance compared with other softwood species. It is also more sensitive to variations in humidity and dryness than hardwood. The wood is very rot-resistant and resilient

Brinell hardness 1,9-2,5 HB

Douglas density is approx 590 kg / m³ as air dry

GRADES

- Natural (photos)
- Vintage

DIMENSIONS

Thickness: 14,5 mm

Width: 230 mm

Length: 2000/2180/2500 mm

Surface layer: 3,5 mm

Weight: 10 kg/m²

STRUCTURE

- 1-strip
- 0,7 mm micro bevels on two long sides
- 0,5 mm micro bevels on two short sides
- 3-layer cross glued engineered wooden flooring
- Middle layer Finnish birch plywood
- Bottom layer Finnish spruce






Standard product birch plywood middle layer

SURFACE TREATMENT

- Hard wax oiled
- Brushed

INSTALLATION

Floating installation (with underlay material) or glued down to subfloor (concrete or plywood)



Locking system WiseLoc / Traditional Tongue and Groove

Suitable with underfloor heating

WiseLock 5G

QUALITY

- FINNISH quality work produced from beginning to end in Finland
- ALLERGY LABEL only wooden flooring certified by Finnish Allergy, Skin and Asthma Federation
- PEFC wooden raw material comes from certified and sustainably managed forests
- CE products fulfill the EU's safety regulation directives
- JAS2 glue seams fulfills the toughest bonding standards
- JAS F**** formaldehyde emission test's highest and toughest standard



JAS2













