



Design floor PUNOS by Joanna Laajisto
(Oak in the pictures)

WOOD SPECIES: Oak and Ash

GRADES:

OAK:

Select grade is carefully selected, more evenly coloured, and almost knotless. The grade allows the filling of pin knots, the natural reflective pattern of oak, i.e., the pattern created by the medullary rays of the tree, and the colour variation caused by the grain pattern.

Design grade is assorted grade with natural variation in colour and small knots may be present.

ASH:

Classic is assorted natural-looking grade in which the natural grain pattern and colour variation of the wood, as well as individual small dark knots, are clearly visible. Small knots may be present.


DIMENSIONS

- Thickness: 14 mm standard
- One plate width x length: 770x770mm
- Top layer 3 mm standard, Oak on request 6 mm
- Weight: 10 kg/m²

STRUCTURE

- 3-layer cross glued engineered wooden flooring
- Middle layer Finnish birch plywood 9 mm
- Bottom layer Finnish spruce 2 mm
- Top layer 3 mm, Oak on request 6 mm
- tongue and groove on all sides

3 mm
9 mm
2 mm



Standard product: Birch plywood structure

SURFACE TREATMENT

- UV hardened matt lacquer/wax oiled
- Sanded surface
- Available tones:
 - Oak: Antique, Cognac, Eben, Luosto, Lyngen, Matte lacquered, Nordic, Sky White, Snöhetta, Wax Oiled, White Matte Lacquered and Untreated.
 - Ash: Eben, Matte Lacquered, Snow White, Wax Oiled, White matte lacquered, White wax oiled and Untreated.

INSTALLATION

- Traditional glued T&G on all four sides
- installation with glueing down to subfloor (concrete or plywood base)
- Suitable with underfloor heating

QUALITY

- FINNISH quality work - produced from beginning to end in Finland
- ALLERGY LABEL - only wooden flooring certified by Finnish Allergy, Skin and Asthma Federation
- PEFC - wooden raw material comes from certified and sustainably managed forests
- JAS2 - Japanese glue seam standard, tolerates the boiling test
- JAS F**** - the highest formaldehyde standard in the world, Timberwise uses the formaldehyde free EPI glue
- M1 - Finnish Building material emission standard
- For lacquered products fire classification Bfl-1s available on request
- Antibacterial treatment available on request



DESIGN FLOOR PUNOS BY JOANNA LAAJISTO
Oak Design grade Uncolored wax oil, sanded, hard wax oiled



DESIGN FLOOR PUNOS BY JOANNA LAAJISTO

Oak Design grade Luosto, sanded, hard wax oiled





DESIGN FLOOR PUNOS BY JOANNA LAAJISTO
Oak Design grade Luosto, sanded, hard wax oiled