



Design floor SALMIAKKI

WOOD SPECIES: Oak and Ash

GRADES:

OAK: Design grade is assorted grade with natural variation in colour and small knots may be present.

ASH:

Classic is assorted natural-looking grade in which the natural grain pattern and colour variation of the wood, as well as individual small dark knots, are clearly visible. Small knots may be present.

DIMENSIONS

- Thickness: 14 mm standard
- Width **one piece** 150mm
- Length-sides: **one piece** 346 x 173 x 173 x 173 mm
one pattern (consist of six pieces): 520 x 520 x 520 x 520 mm
- Top layer 3 mm standard
- Weight: 9,7 kg/m²

STRUCTURE

- 3-layer cross glued engineered wooden flooring
- Top layer 3 mm standard,
- Middle layer Finnish birch plywood 9 mm
- Bottom layer Finnish spruce 2 mm

3 mm
9 mm
2 mm



Standard product: Birch plywood structure

SURFACE TREATMENT

- UV hardened matt lacquer/wax oiled
- Sanded /brushed

INSTALLATION

- Traditional glued T&G on all four sides
- installation with glueing down to subfloor (concrete or plywood base)
- Suitable with underfloor heating

QUALITY

- FINNISH quality work - produced from beginning to end in Finland
- ALLERGY LABEL - only wooden flooring certified by Finnish Allergy, Skin and Asthma Federation
- PEFC - wooden raw material comes from certified and sustainably managed forests
- JAS2 - Japanese glue seam standard, tolerates the boiling test
- JAS F**** - the highest formaldehyde standard in the world, Timberwise uses the formaldehyde free EPI glue
- M1 - Finnish Building material emission standard
- For lacquered products fire classification Bfl-Is available on request



Design floor SALMIAKKI
(Oak in the picture)

