

QUALITY WOODEN FLOORS FROM FINLAND

WOOD SPECIE

ropean White Oak.

- Classic (photos) - Vintage

GRADES - Select

Oak is a hard, heavy and fairly straight grained

wood. It is warm brown in colour and the colour of the heartwood darkens with time. In relation to its weight, oak's moisture-induced shrinkage/expansion is minimal, and it has always been a popular wood for interior decoration. Timberwise uses Eu-

NOTE! The surface treatment might affect to the tone and outlook of the putty area.

Brinell hardness approx. 3.4 to 4.1 HB.

FLOOR FOR LIFE

Oak EBEN (tone)

(The image is always for reference, a sample piece must be ordered.)



DIMENSIONS

- Thickness: 14,0 mm
- Width (standard width bolded): 150/185/230/270 mm
- Length (standard length bolded): 1818/2000/2080/2180 mm (always one length/package)
- Surface layer: 3,0 mm +/- 0,3mm
- Weight: 9,9 kg/m²

STRUCTURE

- 1-strip
- 0,7 mm micro bevels on long sides
- 0,5mm micro bevels on short sides
- 3-layer cross glued engineered wooden flooring
- Wear layer 3,0 mm solid oak
- Middle layer Finnish birch plywood 9,0mm
- Bottom layer Finnish spruce 2,0mm

SURFACE TREATMENT

- UV hardened matte lacquer / wax oil
- Brushed

INSTALLATION

- Floating installation (with underlay material) or glued down to subfloor (concrete or plywood)
- Locking system WiseLoc / Traditional Tongue and Groove
- Suitable with underfloor heating

QUALITY

- FINNISH guality work produced from beginning to end in Finland
- ALLERGY LABEL only wooden flooring certified by Finnish Allergy, Skin and Asthma Federation
- PEFC wooden raw material comes from certified and sustainably managed forests
- JAS2 Japanese glue seam standard, tolerates the boiling test
- JAS F^{****} the highest formaldehyde standard in the world, Timberwise uses the formaldehyde free EPI glue
- M1 Finnish Building material emission standard
- For lacquered products fire classification Bfl-1s available on request
- Antibacterial treatment available on request

JAS2



Standard product birch plywood construction

















9.0 mm 2,0 mm

3,0 mm

Oak EBEN (in picture Classic grade)

1.016

