

LARCH waxoiled

(pictures for reference only, samples must be ordered separately)



WOOD SPECIES

Larch is a highly valued softwood. Its heartwood is reddish-brown, while the sapwood is light in color. Larch is more resistant to wear than pine. It is characterized by significant color variations and knottiness.

Brinell hardness ~ 1.9-2.5 HB

PRODUCT

Larch showcases the natural grain pattern and color variation of the wood. In addition to natural knots, it features knot and cracks filled with brown putty, as well as round knot marks and oval patches. The colour varies naturally from a light yellowish tone to a reddish colour, and the rustic appearance of the grade evens out the variation.

DIMENSIONS (2.42 m² per package, 96.8 m² per pallet)

- Thickness: 14 mm
- Width: 185 mm
- Length: 2180 mm, supporting lengths of 1818 - 2080 mm also allowed (only one length per package)
- Top layer: 3 mm
- Weight: 9.6 kg/m²

STRUCTURE

- 1-strip wooden floor
- 0.7 mm micro bevels on the long sides,
- 0.5 mm micro bevels on the short sides
- Three-layer cross-glued structure:
- Top layer 3 mm solid larch
- Middle layer: plywood, 9 mm
- Bottom layer: Finnish spruce, 2 mm

3.0 mm
9.0 mm
2.0 mm



Standard products have a plywood structure

SURFACE TREATMENT OPTIONS

- UV-harneded wax oil
- brushed surface

INSTALLATION OPTIONS

- Floating installation (with underlay material) or glued down to subfloor (concrete or plywood)
- Locking system WiseLoc (must be glued in tongue and groove / Traditional Tongue and Groove)
- Suitable with underfloor heating



QUALITY

- FINNISH quality – produced from start to finish in Finland, a Key Flag Symbol product
- PEFC – our timber comes from certified forests
- CE – our products fulfil the safety requirements of the applicable EU directives
- M1 – the best possible emission classification



Larch wax oiled

