



Design floor Oak CHEVRON 45°  
150 x 650 mm

### INFO

Timberwise uses European oak and ash, which always come from PEFC-certified forests in Central Europe.

Available in all Timberwise shades.

Available in all Timberwise wood species.

### GRADES

Please see separate grading product card.

### DIMENSIONS

- Thickness: 14 mm
- Width: 150 mm
- Length: 650 mm
- Top layer 3 mm
- Weight: 9,9 kg/m<sup>2</sup>

### STRUCTURE

- 1-strip
- 0,7 mm micro bevels on all four sides or two long sides
- 3-layer cross glued engineered wooden flooring
- Middle layer Finnish birch plywood 9 mm
- Bottom layer Finnish spruce 2 mm
- Top layer 3 mm

3,0 mm  
9,0 mm  
2,0 mm




Standard product: Birch plywood structure

### SURFACE TREATMENT

- UV hardened matt lacquer/wax oiled
- Sanded/Brushed

### INSTALLATION

- Traditional glued T&G, two handed product
- Tongues and grooves are treated with moisture rejecting wax in order to protect seams
- Installation with glueing down to subfloor
- Suitable with underfloor heating
- Chevron 60° by special order



### QUALITY

- FINNISH quality work - produced from beginning to end in Finland
- PEFC - wooden raw material comes from certified and sustainably managed forests
- CE - products fulfill the EU's safety regulation directives
- JAS2 - glue seams fulfills the toughest bonding standards
- JAS F\*\*\*\* - formaldehyde emission test's highest and toughest standard
- Allergy Label from Finnish Allergy, Skin and Asthma Federation - only producer granted with the label





DESIGN FLOOR CHEVRON 45° 150 x 650 mm

Oak Classic, brushed, wax oiled







## MEASURES CHEVRON

