

Design floor DOUBLE HERRINGBONE



WOOD SPECIES & GRADES: OAK, ASH, LARCH

Select, Classic, Natural

Select grade is carefully selected, more evenly coloured, and almost knotless. The grade allows the filling of pin knots, the natural reflective pattern of oak, i.e., the pattern created by the medullary rays of the tree, and the colour variation caused by the grain pattern.

Classic/Natural is a natural-looking grade in which the natural grain pattern and colour variation of the wood are clearly visible. The natural knottness of wood with a few small knots is allowed within the Classic grade. The Classic grade also allows small knot groups, the so-called cat paws, as well as the filling of knots and the natural reflective pattern of oak, i.e., the pattern created by the medullary rays of the tree. **NOTE!** The surface treatment might affect to the tone and outlook of the putty area.

Vintage & Olive

The Vintage grade contains filled cracks and healthy black knots of various sizes. The number of knots, filled knots, and filled cracks varies. Black fillings are part of a genuine vintage look. **The Olive** grade has been named after the dark heartwood, which is also called "olive". The variation in appearance between different boards may be significant, and some of the boards may be without the dark heartwood. Knots, knot groups and filling of knots are also allowed for this grade.

DIMENSIONS

- Thickness: 14 mm standard
- Width x length: 80 x 480 mm, 110 x 660 mm, 150 x 900 mm, 185 x 925 mm
- Top layer 3 mm standard
- Weight: 9,7 kg/m²

STRUCTURE

- 3-layer cross glued engineered wooden flooring
- Top layer 3 mm standard
- Middle layer Finnish birch plywood 9 mm
- Bottom layer Finnish spruce 2 mm

3 mm
9 mm
2 mm



Standard product: Birch plywood structure

SURFACE TREATMENT

- UV hardened matt lacquer/wax oiled
- Sanded /brushed
- Available in all Timberwise Oak, Ash and Larch colors

INSTALLATION

- Traditional glued T&G on all four sides
- installation with glueing down to subfloor (concrete or plywood base)
- Suitable with underfloor heating

QUALITY

- FINNISH quality work - produced from beginning to end in Finland
- ALLERGY LABEL - only wooden flooring certified by Finnish Allergy, Skin and Asthma Federation
- PEFC - wooden raw material comes from certified and sustainably managed forests
- JAS2 - Japanese glue seam standard, tolerates the boiling test
- JAS F**** - the highest formaldehyde standard in the world, Timberwise uses the formaldehyde free EPI glue
- M1 - Finnish Building material emission standard
- For lacquered products fire classification Bfl-1s available on request
- Antibacterial treatment available on request



JAS2

JAS
F****





Design floor DOUBLE HERRINGBONE
Oak Classic NORDIC, brushed hard wax oiled



Design floor DOUBLE HERRINGBONE
Oak Classic NORDIC, brushed hard wax oiled